

REMARKS

The above-noted amendments to the claims are respectfully submitted prior to initiation of the prosecution of the above-identified application in the U.S. Patent and Trademark Office. The amendments to the Specification and a new Abstract are respectfully submitted in order to place the application in compliance with the requirements of U.S. practice. The amendments to the claims are respectfully submitted in order to clarify the subject matter to which the present invention is specifically directed, and to again comply with all the requirements of U.S. practice. No new matter is included in any of these amendments.

It is therefore submitted that the application is now clearly in condition for initiation of prosecution in the U.S. Patent and Trademark Office, and such action is therefore respectfully solicited. If, however, for any reason the Examiner does not believe such action can be taken, it is respectfully requested that the Examiner telephone applicant's attorney at (908) 654-5000 in order to overcome any objections thereto.

Finally, if there are any additional charges in connection with this requested amendment, the Examiner is authorized to charge Deposit Account No. 12-1095 therefor.

Dated: June 21, 2007

Respectfully submitted,

By 

Arnold H. Krumholz

Registration No.: 25,428

LERNER, DAVID, LITTENBERG,

KRUMHOLZ & MENTLIK, LLP

600 South Avenue West

Westfield, New Jersey 07090

(908) 654-5000

Attorney for Applicant



TWIN-WIRE PRESS

FIELD OF THE INVENTION

[0001] The present invention relates to a twin-wire press for dewatering of a fibrefiber suspension.

BACKGROUND OF THE INVENTION

[0002] Twin-wire presses for dewatering of a fibrefiber suspension and forming of a continuous web thereof are previously known. Dewatering of the pulp is usually done from an inlet pulp concentration of 3-8 percentages by weight to an outlet pulp concentration of 30-50 percentages by weight. According to the state of the art, such twin-wire presses comprises lower rolls, an endless lower wire running in a path around the lower rolls, upper rolls, and an endless upper wire running in a path around the upper rolls. The two wires co-operate with each other along sections of said paths that run substantially in parallel with each other for dewatering of the fibrefiber suspension between the wires during displacement thereof. An inlet box provides for supply of the fibrefiber suspension to a wedge-shaped dewatering space between the wires. The twin-wire press further comprises two dewatering tables supporting the respective wire in said sections of the path and forming the wedge-shaped dewatering space between the wires for initially pressing and dewatering the fibrefiber suspension, whereby a web is formed between the wires, and a roll arrangement situated after the dewatering tables in said sections of the paths, as seen in the direction of movement of the wires, for finally pressing and dewatering the web between the wires, so that the web will get a desired dryness.

[0003] It is often necessary in a simple way and as quickly as possible at maintenance, exchange of wire and cleaning of the twin-wire press, without prolonged stoppage of

production, to be able to reach the dewatering space between the upper and lower dewatering tables. An apparatus for lifting of the upper table in twin-wire presses is known, which is a lifting apparatus integrated in the press that is arranged to lift up the side of the upper dewatering table, hereinafter denoted the front edge, that is adjacent the roll arrangement. A rear edge of the dewatering table remains in the original position. The known lifting apparatus only permits a limited lifting of the upper dewatering table, and only of its front edge, which means that the accessibility to those areas of the dewatering space that are situated in vicinity of the rear edge of the upper and lower dewatering tables still are restricted, whereby maintenance, exchange of wire and cleaning is time-consuming and circumstantial.

[0004] ~~The~~ One object of the present invention is to achieve an easier, more effective and improved twin-wire press where the whole dewatering space is easily accessible for maintenance, exchange of wire and cleaning if required, and where at least those drawbacks that are associated with previously known state of the art can be partially eliminated. ~~Yet an~~ Another object is to provide a twin-wire press where maintenance, exchange of wire and cleaning of the press can be carried out cost efficiently and in a work saving way.

SUMMARY OF THE INVENTION

[0005] ~~These~~ In accordance with the present invention, these and other objects are achieved with the twin-wire press for dewatering of a ~~fibrefiber~~ suspension ~~according to the present invention~~. The twin-wire press comprises lower rolls, an endless lower wire that runs in a path around the lower rolls, upper rolls and an endless upper wire that runs in a path

around the upper rolls. Further the twin-wire press comprises first and a second dewatering table, respectively, which supports the respective upper and lower wires, which dewatering tables forms a wedge-shaped dewatering space between the wires in the longitudinal direction of the twin-wire press for initial pressing and dewatering of the fibrefiber suspension. In that respect a fibrefiber web can be formed between the wires, and a roll arrangement is provided and positioned after the dewatering tables, as seen in the direction of movement of the wires, for finally pressing and dewatering of the fibrefiber web between the wires. The roll arrangement is provided in a press frame. A press and lift arrangement is arranged to the first dewatering table for vertically adjusting the first dewatering table. The twin-wire press is characterised in that a link system is arranged in one end with a joint at the press frame and in a second end arranged with a joint at an upper section of the first dewatering table. In that respect the first dewatering table can be moved along its whole longitudinal extension in direction from and against the second dewatering table by movement by means of the press and lift arrangement.

[0006] The present invention makes it possible that work with maintenance, exchange of wire and cleaning of the twinwire press can be carried out efficiently whereby the operation of the press only need to be interrupted for a short period than what has been required previously. Hence, time and cost savings are obtained thanks to that the whole first dewatering table can be lifted or lowered along its whole longitudinal extension, in the twin-wire press according to the present invention, such that desired accessibility to the dewatering space can be provided between the whole

longitudinal extension of the first dewatering table and the whole longitudinal extension of the second dewatering table.

[0007] According to a preferred embodiment of the present invention, an end section of the press and lift arrangement is fixed to the press frame and a second end section of the press and lift arrangement is arranged to the first dewatering table. In that respect the press and lift arrangement is suitably arranged in vicinity of a front edge of the first dewatering table. Preferably the press and lift arrangement is arranged at a projecting section of the press frame, at a position on distance from the dewatering space connection to an upper section of the first dewatering table. The press and lift arrangement is preferably a hydraulic cylinder. The link system may suitably comprise a link arm that in one end is pivotally arranged in the first dewatering table, and in a second end is pivotally arranged in said joint at the press frame. Preferably the first dewatering table is composed of an upper dewatering table and the second dewatering table of a lower dewatering table.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The present invention will now be described in more detail by embodiments, with reference to accompanying drawings, without restricted interpretation of the invention thereof, where

[0009] fig. 1 schematically shows in an overview a longitudinal cross-section through a twin-wire press according to an embodiment of the present invention.

DETAILED DESCRIPTION

[0010] A twin-wire press 2 for dewatering of a ~~fibrefiber~~ suspension is shown in fig. 1. The twin-wire press comprises lower rolls 4 (in the figure is only shown one of the lower rolls), an endless lower wire (not shown)

that runs in a path around the lower rolls, upper rolls 6 (in the figure is only shown one of the upper rolls) and an endless upper wire (not shown) that runs in a path around the upper rolls. Further the twin-wire press 2 comprises a first dewatering table, here shown as an upper dewatering table 8, respectively a second dewatering table, here shown as a lower dewatering table 10, which supports the respective upper and lower wires, which dewatering tables 8, 10 forms a wedge-shaped dewatering space 12 between the wires in the longitudinal direction L1 of the twin-wire press for initial pressing and dewatering of the ~~fibrefiber~~ suspension, whereby a ~~fibrefiber~~ web can be formed between the wires. A roll arrangement 14 (only pair of rolls 4, 6 is shown in fig. 1) is arranged after the dewatering tables 8, 10, seen in the direction of movement (F) of the wires, for final pressing and dewatering of the ~~fibrefiber~~ web between the wires. The roll arrangement 14 is provided in a press frame 16. A press and lift arrangement 18 is arranged to the upper dewatering table 8 for vertically adjusting the upper dewatering table. A link system 20 is arranged in one end with a joint 22 at the press frame 16 and in another end arranged with a joint 24 at an upper section 26 of the upper dewatering table 8. The upper dewatering table 8 can be moved along its whole longitudinal extension L2 in a vertical direction T from and against the longitudinal direction L1 of the lower dewatering table 10 by movement by means of the press and lift arrangement 18. The twin-wire press may preferably comprise a corresponding link system and a press and lift arrangement as described herein, according to the present invention, on each side of the twin-wire press (in fig. 1 is only shown one side of the twin-wire press).

[0011] By reference to fig. 1 is described that the first dewatering table is an upper dewatering table 8 and the second dewatering table is a lower dewatering table 10. However, the situation can be the opposite according to an alternative embodiment. If the whole twin-wire press as shown in fig. 1 is viewed upside-down (from a direction B according to arrow in fig. 1), said first dewatering table is composed of a lower dewatering table 8' and said second dewatering table is composed of an upper dewatering table 10'. Thus, according to this embodiment is the press and lift arrangement 18 and the link system 20 arranged to the lower dewatering table 8'. Hence, a vertical adjustment is instead achieved of the lower dewatering table 8'.

[0012] Different kinds of press and lift arrangements 18 that can be used in the present invention are possible. The press and lift arrangement can, for example, as shown in fig. 1, preferably be a hydraulic cylinder, that has a piston 28 with, a certain cylinder stroke arranged in a liquid filled, such as oil filled, cylinder 30.

[0013] An end section of the press and lift arrangement 18 can suitably be fixed to the press frame 16 according to the embodiment shown in fig. 1, such as an outer end of the piston 28 of said preferred hydraulic cylinder. A corresponding second end section of the press and lift arrangement, such as the outer end section of the cylinder portion 30 of the preferred hydraulic cylinder, can be arranged to the upper dewatering table 8. As is evident from fig. 1, the press and lift arrangement 18 can be arranged in the vicinity of a front edge 32 of the upper table 8. One end of the press and lift arrangement may suitably be connected to a projecting section 34 of the press frame, situated in connection to an upper section 26 of the upper dewatering table 8 on distance from the dewatering space 12. The other end of

the press and lift arrangement is connected to the upper dewatering table, suitably in a position in vicinity of the front edge of the dewatering table. Further, the press frame may comprise a stop member 36 arranged on a surface 38 of the press frame in the space between the press frame and the front edge of the upper table, which stop member 36 prevents movement of the upper dewatering table 8 in the longitudinal direction L1 of the twin-wire press at vertical adjustment of the upper dewatering table. The stop member 36, that is suitably of a durable material having low friction, can be shaped as a projecting section with a supporting surface directed against the front edge 32 of the upper dewatering table. At vertical adjustment in direction T of the upper dewatering table 8 the front edge 32 of the upper dewatering table can slide along the supporting surface of the stop member 36.

[0014] Further, the link system 20 according to the present invention can comprise a link arm 40 that in one end is pivotally arranged in said joint 24 at the upper dewatering table 8, suitably to the upper side 42 of the upper dewatering table 8 in immediate connection to the front edge 32 of the upper dewatering table, and in a second end pivotally arranged in said joint 22 at the press frame 16, such as is shown in fig. 1.

[0015] When the press and lift arrangement 18 is actuated, for example at a reduced cylinder stroke when using a preferred hydraulic cylinder, for a desired raise of the upper dewatering table 8, the dewatering table 8 is raised along its whole longitudinal extension L2 by a simultaneous turning of the link arm 20 around joints 24 and 22 of the link system 20 (see arrow P1 in figure). A rear edge 44 of the upper dewatering table 8 is raised substantially equally as much as the front edge 32 (see arrow P2 in figure).

The front edge 32 slides during the vertical movement of the dewatering table against the stop member 36 that simultaneous prevents that no substantial motion of the dewatering table 8 along the longitudinal direction L1 of the twin-wire press occurs. An increased distance A between the lower and upper dewatering tables may accordingly be achieved, along the whole longitudinal extension L2 of the dewatering space, in order to facilitate desired accessibility for maintenance, exchange of wire and cleaning when necessary.

[0016] Fig. 1 also shows schematically the position for an apparatus 46 for elevation of the upper table in twin-wire presses according to the prior art, which is an integrated lifting device in the press that is arranged to raise up the front side of the upper dewatering table, that is faced to the roll arrangement. The known lifting device only permits a limited elevation of the front side of the upper dewatering table.

[0017] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.